

HWUACP8

Barrier-Free Wall Mounted Electric Drinking Fountain



FEATURES & BENEFITS

No features or benefits found.

OPTIONS

No options found.



SPECIFICATIONS

Haws model HWUACP8 pressure drinking water cooler shall deliver a minimum of 8 gph (30.3 LPH) of water at 50°F (10°C) cooled from 80°F (26.7°C) inlet water at 90°F (32.2°C) ambient. Front and side mounted push pads requiring less than 5 pounds of force to activate that initiate water flow through a flexible hooded rubber bubbler having a non-squirt feature. An internally mounted valve and adjustable stream regulator shall control water flow between 20 and 90 psig. R-134a refrigeration system shall be hermetically sealed and refrigerant flow shall be capillary tube controlled. An adjustable thermostat having an off position shall control refrigeration system. Stainless steel top shall have integral drain strainer. Heavy-duty galvanized frame shall support Sandstone powder-coated galvanized exterior panels. Built-in 100 micron strainer and external stream height adjustment are enclosed by a removable lower panel which provides easy access

APPLICATIONS

Perfect for either public or private settings, our barrier-free electric water coolers are a great fit in indoor environments. This series is precisely mounted, making it a nice addition to any surrounding. Beautiful satin finish basin help to maintain the fountains overall appeal so it always remains looking as new as it did when it was installed. Specifically, this type fountain may be placed in settings such as: office buildings, shopping malls, and other indoor environments where there is a demand for a chilled water source and/or wheel chair access.



318 East 8th Street | P.O. Box #189 | La Crosse, KS 67548
Ph: 785-222-2515 | TF: 888-846-2693 | Fax: 866-436-7601